

Hand pallet truck **LEC2300™**



The perfect basis for all transport systems

The Lift-Rite Hand pallet truck is the perfect basis for all transport systems involving palletized goods and materials. Versatile, convenient and reliable, it does its job well in every environment. With its high quality and reliability, Lift-Rite offers many years of problem-free pallet handling. Excellent ergonomic properties guarantee safe, user-friendly handling.

Hand pallet truck **LEC2300™**



Bushings, grease bushings and ground axes for high performance in the long term.



Rugged, robust pump for high reliability.

Benefits and features:

- Easy to steer and manoeuvre because of 180° steering angle.
- Easy to pump because of high quality and design.
- Easy pallet entry thanks to rounded fork tips and front climber wheels.
- Easy to handle because of low weight.
- Reliable and robust fork frame made of high strength steel.

Technical Details LEC2300™

Capacity	_____	2300 kg
Pump strokes to full height	___	12
Truck weight	_____	65 kg
Width across forks	_____	520/685 mm
Fork length	_____	800/910/1000/1070/ _____
	_____	1150/1220 mm
Min fork height	_____	85 mm
Max lifting height	_____	200 mm



Many wheel options.

Wheel alternatives:

Nylon

These wheels roll very easily because of their hard surface and are suitable for hard, smooth floors. They are especially good to use when the truck is heavily loaded. These wheels are used in all kinds of applications and are non-marking.

Polyurethane

This wheel has a tread of polyurethane and a rim of nylon. It is quieter than a nylon wheel and works best with loads under 1200 kg. Above that weight the machine will be harder to pull. The polyurethane wheel can be used in all kinds of applications.

Rubber

Tread of rubber and rim of nylon. This wheel is only available as steering wheel. Because of its soft tread, heavy loads should be avoided. Typical applications where this wheel could be used are wet/slippery floors and where quiet running is essential.

Powerthane

Combines the features of a polyurethane and rubber wheel. The Powerthane wheel has the same low friction and silent running as a rubber wheel but is similar in hardness to the polyurethane wheel. This gives it better durability than a rubber wheel. Non-marking.

Steel

An easy-rolling wheel for bad floor conditions or floors with swarf or other things that could stick to the wheel. The most common application is in heavy industry, e.g. foundries.